Alle prijzen en specificaties kunnen zonder kennisgeving worden gewijzigd. Voor de meest actuele data, raden wij U steeds aan de website van Acer te raadplegen. 2Compute is niet verantwoordelijk voor eventuele tekstuele en/of inhoudelijke fouten in dit document. De gebruikte foto's dienen enkel als referentie en kunnen afwijken van het daadwerkelijke product.

2Compute, uw AcerPoint van vertrouwen

2Compute bvba, Schooldreef 73-75, B-9050 Gentbrugge - Tel: 09 232 10 73 - Email: info@2compute.be - BTW: BE 0462.510.945 - Webshop: www.2compute.net

Transport : 10€ OF Afhalingen : 0€

2Compute Online Shop www.2Compute.net

Ean-code	Artikelcode Acer	Omschrijving

Value Projector

Specifications

Display: DLP ™
Resolution: Native SVGA (800 x 600),
Maximum UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)
Aspect Ratio: 4:3 Native, 16:9 Compatible
Contrast Ratio: 10.000:1
3D ready: With DLP 3D ready, user can view any 120 Hz 3D frame sequential content from a PC with appropriate 120 Hz graphic card and 3D stereoscopic player or any HQFS 3D DVD title from an NTSC DVD player by wearing a DLP 3D glasses
Displayable Colors: 1.07 Billion Colors
Brightness: 2,700 ANSI Lumens (Standard), 2,160 ANSI Lumens (ECO)
Projection Lens: F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm
Manual Zoon and Focus
Projection Screen Size (Diagonal): 24" (58cm) ~ 300" (762cm)
Projection Distance: 3.3' (1.0m) ~ 39.0' (11.9m)
Throw Ratio: 53"@2m (1.86 ~ 2.04:1)
Horizontal Scan rate: 30k ~ 100k Hz
Vertical Refresh Scan Rate: 50 ~ 120 Hz
Lamp Type: Osram 190 W user replaceable P-VIP lamp
Lamp Life: 5,000 Hours (Standard), 6,000 Hours (ECO)
Keystone Correction: +/-40 Degrees (vertical)
Projection mode: Front, Rear, Front-Ceiling, Rear-Ceiling
Weight: 4.4 lbs (2.0 Kg)
Wireless Dongle Compatible: NO
Digital Zoom: 2x
Input: D-Sub / Composite Video (RCA) / S-Video (Mini DIN)
Dimension:264 x 220 x 78 mm (10.4" x 8.7" x 1.3")
Remote Control: Infra red
Power Supply: AC Input 100~240V auto-switching power supply
Power Consumption: 240 Watts (Operation), <1 Watts (Standby)
Operating Temperature: 0°C ~ 40°C / 32°F ~ 104°F
Noise Level: 30 dBA (Standard mode), 26 dBA (ECO mode)
Uniformity: 85%

IBM PC and Compatibles, Apple iMac/MacBook, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
DLP 3D ready
With DLP 3D ready, user can view any 120 Hz 3D frame sequential content from a PC with appropriate 120 Hz graphic card and 3D stereoscopic player by wearing a DLP 3D glasses

4717276669393	MR.JER11.001	X1140A (3D) - DLP™ - SVGA 800 x 600 - 10.000:1 - 2700 ANSI Lumens - Analog - 2x Digital Zoom - CBII - Autokeystone - DLP 3D - SpectraBoost - 30dB - 2.5KG - Bag - Eco

Specifications

Display: DLP ™
Resolution: Native XGA (1,024 x 768)
Maximum UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)
Aspect Ratio: 4:3 Native, 16:9 Compatible
Contrast Ratio: 10.000:1
3D ready: With DLP 3D ready, user can view any 120 Hz 3D frame sequential content from a PC with appropriate 120 Hz graphic card and 3D stereoscopic player or any HQFS 3D DVD title from an NTSC DVD player by wearing a DLP 3D glasses
Displayable Colors: 1.07 Billion Colors
Brightness: 2,700 ANSI Lumens (Standard), 2,160 ANSI Lumens (ECO)
Projection Lens: F = 2.56 ~ 2.8, f = 21.00mm ~ 23.00mm
1:1.1 Manual Zoom and Manual Focus
Projection Screen Size (Diagonal): 24" (61cm) ~ 300" (762cm)
Projection Distance: 3.3' (1.0m) ~ 37.2' (11.3m)
Throw Ratio: 53"@2m (1.86 ~ 2.04:1)
Horizontal Scan rate: 30k ~ 100k Hz
Vertical Refresh Scan Rate: 50 ~ 120 Hz
Lamp Type: Osram 190 W user replaceable P-VIP lamp
Lamp Life: 5,000 Hours (Standard), 6,000 Hours (ECO), 7,000 Hours (ExtremeEco)*
Keystone Correction: +/-40 Degrees (vertical)
Projection mode: Front, Rear, Front-Ceiling, Rear-Ceiling
Weight: 4.4 lbs (2.0 Kg)
Wireless Dongle Compatible: NO

Digital Zoom: 2x
Spectraboost: 30% of NTSC color gamut increment, delivering outstanding color saturation
Input: D-Sub / Composite Video (RCA) / S-Video (Mini DIN)
Dimension: 264 x 220 x 78 mm (10.4" x 8.7" x 1.3")
Remote Control: Infra red
Power Supply: AC Input 100~240V auto-switching power supply
Power Consumption: 240 Watts (Operation), <0.5 Watts (Standby)
Operating Temperature: 0°C ~ 40°C / 32°F ~ 104°F
Noise Level: 30 dBA (Standard mode), 26 dBA (ECO mode)
Uniformity: 85%

IBM PC and Compatibles, Apple iMac/MacBook, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
DLP 3D ready
With DLP 3D ready, user can view any 120 Hz 3D frame sequential content from a PC with appropriate 120 Hz graphic card and 3D stereoscopic player by wearing a DLP 3D glasses

4712196226152 MR.JF211.003 X1240, DLP™ - XGA 1024 x 768 - 10.000:1 - 2700 ANSI Lumens - Analog - 2x Digital Zoom - CBII+ - Autokeystone - DLP 3D - SpectraBoost - 30dB - 2.5Kg - Bag - ECO

Specifications

Display: DLP ™
Resolution: Native WXGA (1,280 x 800)
Maximum UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)
Aspect Ratio: 16:10 (Native), 4:3, 16:9
Contrast Ratio: 10.000:1
3D ready: With DLP 3D ready, user can view any 120 Hz 3D frame sequential content from a PC with appropriate 120 Hz graphic card and 3D stereoscopic player or any HQFS 3D DVD title from an NTSC DVD player by wearing a DLP 3D glasses
Displayable Colors: 1.07 Billion Colors
Brightness: 2,700 ANSI Lumens (Standard), 2,160 ANSI Lumens (ECO)
Projection Lens: F = 2.56 ~ 2.8, f = 21.00mm ~ 23.00mm
1:1.1 Manual Zoom and Manual Focus
Projection Screen Size (Diagonal): 34" (86cm) ~ 300" (762cm)
Projection Distance: 3.9' (1.2m) ~ 31.8' (9.7m)
Throw Ratio: 62"@2m (1.50 ~ 1.65:1)
Horizontal Scan rate: 30k ~ 100k Hz
Vertical Refresh Scan Rate: 50 ~ 120 Hz
Lamp Type: Osram 180 W user replaceable P-VIP lamp
Lamp Life: 5,000 Hours (Standard), 6,000 Hours (ECO), 7,000 Hours (ExtremeEco)*
Keystone Correction: +/-40 Degrees (vertical)
Projection mode: Front, Rear, Front-Ceiling, Rear-Ceiling
Weight: 5.5 lbs (2.5 Kg)
Wireless Dongle Compatible: NO
Digital Zoom: 2x
Spectraboost: 30% of NTSC color gamut increment, delivering outstanding color saturation
Input: D-Sub / Composite Video (RCA) / S-Video (Mini DIN) / HDMI (Video, Audio, HDCP) x 1
Dimension: 280 x 230 x 84 mm (11" x 9.1" x 3.3")
IR remote control with PgUp/PgDn functions
Power Supply: AC input 100~240V auto-switching power supply
Power Consumption: 246 Watts (Operation), <1 Watts (Standby)
Operating Temperature: 0°C ~ 35°C / 32°F ~ 95°F
Noise Level: 30 dBA (Standard mode), 26 dBA (ECO mode)
Uniformity: 85%
Computer capatibility: IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)

Video Compatibility: NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i), EDTV (480p, 576p), SDTV (480i, 576i)

4712196040482 MR.JET11.001 X1311WH, DLP™ - WXGA 1280 x 800 - 10.000:1 - 2700 ANSI Lumens - Analog & HDMI - 2x Digital Zoom - CBII+ - Autokeystone - Nvidia 3D - SpectraBoost - 30dB - 2.6Kg - Bag -Extreme ECO

Specifications

Display: DLP ™
Native Resolution: SVGA (800 x 600)
Maximum Resolution: UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)
Aspect Ratio: 4:3 Native, 16:9 Compatible
Contrast Ratio: 3000:1
3D ready: With DLP 3D ready, user can view any 120 Hz 3D frame sequential content from a PC with appropriate 120 Hz graphic card and 3D stereoscopic player or any HQFS 3D DVD title from an NTSC DVD player by wearing a DLP 3D glasses
Displayable Colors: 1.07 Billion Colors
Brightness: 2700 ANSI Lumens (Standard), 2160 ANSI Lumens (ECO)
Projection Lens: F = 2.51 ~ 2.69, f = 21.95mm ~ 24.18mm
1:1.1 Manual Zoom and Manual Focus
Projection Screen Size (Diagonal): 23" (58cm) ~ 300" (762cm)
Projection Distance: 3.3' (1.0m) ~ 39.4' (12.0m)
Throw Ratio: 50"@2m (1.97 ~ 2.17:1)
Horizontal Scan rate: 30k ~ 100k Hz
Vertical Refresh Scan Rate: 50 ~ 120 Hz
Lamp Type: Osram 180 W user replaceable P-VIP lamp
lamp Life: 5,000 Hours (Standard), 6,000 Hours (ECO)
Keystone Correction: +/-40 Degrees
Weight: 5.2 lbs (2.34 Kg)
Wireless Dongle Compatible: NO
Digital Zoom 2x
Input Interface: Analog RGB/Component Video (D-sub) x 1 / Composite Video (RCA) x 1
S-Video (Mini DIN) x 1 / HDMI (Video, Audio, HDCP) x 1 / PC Audio (Stereo mini jack) x 1
Output Interface: Analog RGB (D-Sub)
Control Interface: USB (type B) / RS232 (mini DIN)
Dimension: 269 x 206 x 84 mm (10.6" x 8.1" x 3.3")
Remote Control: IR remote control with laser pointer & PgUp/PgDn functions

Power Supply: AC Input 100~240V auto-switching power supply
Power Consumption: 245 Watts (Operation), <1 Watts (Standby)
Operation Temperature: 0°C ~ 35°C / 32°F ~ 95°F
Noise Level: 29 dBA (Standard mode), 27 dBA (ECO mode)
Uniformity: 90%
Computer Compatibility: IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards 1080p (1,920x1,080),
WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768),
UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility: NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L),
HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)

4717276954116	EY.JED04.004	P1120 - DLP™ - SVGA 800 x 600 - 3000:1 - 2700 ANSI Lumens - Analog & HDMI - 2x Digital Zoom - CBII - keystone - DLP 3D - 29dB - 2.3KG - Bag - Eco

Specifications

Native Resolution: Native XGA (1,024 x 768)
Maximum Resolution: UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)
Aspect Ratio: 4:3 Native, 16:9 Compatible
Contrast Ratio: 3700:1
3D ready: With DLP 3D ready, user can view any 120 Hz 3D frame sequential content from a PC with appropriate 120 Hz graphic card and 3D stereoscopic player or any HQFS 3D DVD title from an NTSC DVD player by wearing a DLP 3D glasses
Displayable Colors: 1.07 Billion Colors
Brightness: 2,700 ANSI Lumens (Standard), 2,160 ANSI Lumens (ECO)
F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm
1:1.1 Manual Zoom and Manual Focus
Projection Distance: 23" (58cm) ~ 300" (762cm)
Throw Ratio: 50"@2m (1.95 ~ 2.15:1)
Horizontal Scan rate: 30k ~ 100k Hz
Vertical Refresh Scan Rate: 50 ~ 120 Hz
Lamp Type: Osram 180 W user replaceable P-VIP lamp
lamp Life: 5,000 Hours Standard / 6,000 Eco Mode
Keystone Correction: +/-40 Degrees Manual & Auto
Weight: 5.5 lbs (2.5 Kg)
Wireless Dongle Compatible: NO
Digital Zoom 2x
Input Interface: D-Sub / Composite Video (RCA) / S-Video / PC Audio / HDMI (Video, HDCP) x 1
Output Interface: Analog RGB (D-Sub)
Control Interface: USB (type B) / RS232 (mini DIN)
Dimension: 269 x 206 x 84 mm (10.6" x 8.1" x 3.3")
Remote Control: IR remote control with laser pointer & PgUp/PgDn functions
Power Supply: AC input 100~240V auto-switching power supply
Power Consumption: 255 Watts (Operation), <1 Watts (Standby)
Operation Temperature: 5°C ~ 35°C / 41°F ~ 95°F
Noise Level: 28 dBA (Standard mode), 25 dBA (ECO mode)
Uniformity: 90%
Computer Compatibility: IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)

Video Compatibility: NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)

4717276954154	EY.JEE04.004	P1220 - DLP™ - XGA 1024 x 768 - 3700:1 - 2700 ANSI Lumens - HDMI - 2x Digital Zoom - DPL 3D - CBII+ - CSII - bag - Autokeystone - 2.5Kg - ECO

Professional Projector

Specifications

Display: DLP ™
Native XGA (1024x768), Maximum UXGA (1600 x 1200), WSXGA+ (1680 x 1050)
Aspect Ratio: 4:3 Native, 16:9 Compatible
Displayable Colors: 1.07 Billion Colors
Contrast Ratio: 3200:1
Brightness: 5,000 ANSI Lumens (Standard), 4,000 ANSI Lumens (ECO)
Digital Zoom: 8x
F = 2.45 ~ 2.9, f = 22.18mm ~ 33.27mm
1:1.5 Manual Zoom and Manual Focus
Projection Screen Size (Diagonal): 21" (53cm) ~ 300" (762cm)
Projection Distance: 3.3' (1.0m) ~ 31.0' (9.4m)
Throw Ratio: 64"@2m (1.55 ~ 2.36:1)
Horizontal Scan rate: 27 ~ 92 kHz
Vertical Refresh Scan Rate: 30k ~ 100k Hz
Lamp Type: 350 W user replaceable P-VIP lamp
Lamp Life: 1,500 Hours (Standard), 2,500 Hours (ECO)
Keystone Correction: '+/-40 Degrees (Vertical), +/-15 Degrees (Horizontal), Manual
Audio: 2 Internal Speaker with 3W Output
Weight: 15 lbs / 6.8Kg
Wireless Dongle Compatible: NO
Input Interface: Analog RGB/Component Video (D-sub) x 2 / Composite Video (RCA) x 1
S-Video (Mini DIN) x 1 /Component (3 RCA) x 1 / HDMI (Video, Audio, HDCP) x 2 / DVI (HDCP) x 1
PC Audio (Stereo mini jack) x 2 / USB (Type A) x 2 / USB (Mini B) x 1
Output Interface: Analog RGB (D-Sub) / PC Audio (Stereo Mini Jack) / SPDIF Audio (RCA)
Control Interface: USB (type B) / RS232 (mini DIN) / Wired Remote Control Port (Mini Jack)
12V DC (Screen control) x 1 / Network Interface: Ethernet port (RJ45) x 1
Dimension: 398 x 310 x 130 mm (15.7" x 12.2" x 5.1")
Remote Control: IR & wired remote control with laser pointer & mouse & PgUp/PgDn functions
Power Supply: AC input 100~240V auto-switching power supply
Power Consumption: 460 Watts (Operation), 1 Watts (Standby)
Operation Temperature: 5°C ~ 35°C / 41°F ~ 95°F

Noise Level: 34 dBA (Standard mode), 31 dBA (ECO mode)- w/o dust filter
Uniformity: 90%
Computer Compatability: IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards
WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA
(1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility: NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV
(720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)

[E] 4717276027711 EY.K2501.001 P7203 - DLP™ - XGA 1024 x 768 - 3200:1 - 5000 ANSI Lumens - DVI - HDMI - 8x Digital Zoom - PiP - CBII - 34dB - 6.8kg - Bag - Eco

Specifications

Display: DLP ™
Native XGA (1024x768), Maximum UXGA (1600 x 1200), WSXGA+ (1680 x 1050)
Aspect Ratio: 4:3 Native, 16:9 Compatible
Displayable Colors: 1.07 Billion Colors
Contrast Ratio: 3200:1
Brightness: 5,000 ANSI Lumens (Standard), 4,000 ANSI Lumens (ECO)
Digital Zoom: 8x
F = 2.45 ~ 2.9, f = 22.18mm ~ 33.27mm
1:1.5 Manual Zoom and Manual Focus
Projection Screen Size (Diagonal): 21" (53cm) ~ 300" (762cm)
Projection Distance: 3.3' (1.0m) ~ 31.0' (9.4m)
Throw Ratio: 64"@2m (1.55 ~ 2.36:1)
Horizontal Scan rate: 27 ~ 92 kHz
Vertical Refresh Scan Rate: 30k ~ 100k Hz
Lamp Type: 350 W user replaceable P-VIP lamp
Lamp Life: 1,500 Hours (Standard), 2,500 Hours (ECO)
Keystone Correction: '+/-40 Degrees (Vertical), +/-15 Degrees (Horizontal), Manual
Audio: 2 Internal Speaker with 3W Output
Weight: 15 lbs / 6.8Kg
Wireless Dongle Compatible: Yes
Display over USB (DoUSB) & USB Slide Show (Photos, PowerPoint*) With the USB Slide Show, the projector enables the
Input Interface: Analog RGB/Component Video (D-sub) x 2 / Composite Video (RCA) x 1
S-Video (Mini DIN) x 1 /Component (3 RCA) x 1 / HDMI (Video, Audio, HDCP) x 2 / DVI (HDCP) x 1
PC Audio (Stereo mini jack) x 2 / USB (Type A) x 2 / USB (Mini B) x 1
Output Interface: Analog RGB (D-Sub) / PC Audio (Stereo Mini Jack) / SPDIF Audio (RCA)
Control Interface: USB (type B) / RS232 (mini DIN) / Wired Remote Control Port (Mini Jack)
12V DC (Screen control) x 1 / Network Interface: Ethernet port (RJ45) x 1
Dimension: 398 x 310 x 130 mm (15.7" x 12.2" x 5.1")
Remote Control: IR & wired remote control with laser pointer & mouse & PgUp/PgDn functions
Power Supply: AC input 100~240V auto-switching power supply
Power Consumption: 460 Watts (Operation), 1 Watts (Standby)
Operation Temperature: 5°C ~ 35°C / 41°F ~ 95°F
Noise Level: 34 dBA (Standard mode), 31 dBA (ECO mode)- w/o dust filter
Uniformity: 90%
Computer Compatability: IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards
WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA
(1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility: NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV
(720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)

4717276671921 EY.JCU01.001 P7203B - DLP™ - XGA 1024 x 768 - 3200:1 - 5000 ANSI Lumens - USB Display & Reader - DVI - HDMI - 8x Digital Zoom - PiP - CBII - 34dB - 7.5kg - Bag - Eco

Specifications

Display: DLP ™
Native XGA (1024x768), Maximum UXGA (1600 x 1200), WSXGA+ (1680 x 1050)
Aspect Ratio: 4:3 Native, 16:9 Compatible
Displayable Colors: 1.07 Billion Colors
Contrast Ratio: 2100:1
Brightness: 6,000 ANSI Lumens (Standard), 4,800 ANSI Lumens (ECO)
Digital Zoom: 2x
F = 1.77 ~ 1.93, f = 28.64mm ~ 34.35mm
1:1.2 Manual Zoom and Manual Focus
Projection Screen Size (Diagonal): 25" (64cm) ~ 300" (762cm)
Projection Distance: 4.0' (1.2m) ~ 40.0' (12.2m)
Throw Ratio: 49"@2m (2.00 ~ 2.40:1)
Horizontal Scan rate: 30k ~ 100k Hz
Vertical Refresh Scan Rate: 50 ~ 120 Hz
Lamp Type: Osram 330 W user replaceable P-VIP lamp
Lamp Life: 1,500 Hours (Standard), 2,000 Hours (ECO)
Keystone Correction:'+/-40 Degrees (Vertical), Manual
Audio: 2 Internal Speaker with 3W Output
Weight: 15.6 lbs (7.1Kg)
Wireless Dongle Compatible: NO
Input Interface: Analog RGB/Component Video (D-sub) x 2 / Composite Video (RCA) x 1
S-Video (Mini DIN) x 1 /Component (3 RCA) x 1 / HDMI (Video, Audio, HDCP) x 2 / DVI (HDCP) x 1
PC Audio (Stereo mini jack) x 2 / USB (Type A) x 2 / USB (Mini B) x 1
Output Interface: Analog RGB (D-Sub) / PC Audio (Stereo Mini Jack) / SPDIF Audio (RCA)
Control Interface: USB (type B) / RS232 (mini DIN) / Wired Remote Control Port (Mini Jack)
12V DC (Screen control) x 1 / Network Interface: Ethernet port (RJ45) x 1
Dimension: 398 x 310 x 130 mm (15.7" x 12.2" x 5.1")
Remote Control: IR & wired remote control with laser pointer & mouse & PgUp/PgDn functions
Power Supply: AC input 100~240V auto-switching power supply
Power Consumption: 460 Watts (Operation), 1 Watts (Standby)
Operation Temperature: 5°C ~ 35°C / 41°F ~ 95°F
Noise Level: 34 dBA (Standard mode), 31 dBA (ECO mode)- w/o dust filter
Uniformity: 90%

Computer Compatability: IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards
WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA
(1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility: NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV
(720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)

4712196127497	MR.JEK11.001	P7215 - DLP™ - XGA 1024 x 768 - 2100:1 - 6000 ANSI Lumens - DVI - HDMI - 8x Digital Zoom - PiP - CBII - 34dB - 6.8kg - Bag - Eco

Specifications

Display: DLP ™
Native Full HD (1920x1080), Maximum UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)
Aspect Ratio: 16:9 (Native), 4:3 compatible
Displayable Colors: 1.07 Billion Colors
Color wheel: 6 segments
Contrast Ratio: 40.000:1
Brightness: 4000 ANSI Lumens (standard)
Digital Zoom: 8x
Projection Lens: F = 2.45 ~ 2.9, f = 22.18mm ~ 33.27mm
1:1.5 Manual Zoom and Manual Focus
Projection Screen Size (Diagonal): 20" (50cm) ~ 300" (762cm)
Projection Distance: 3.3' (1.0m) ~ 32.7' (10.0m)
Throw Ratio: 60"@2m (1.50 ~ 2.28:1)
Horizontal Scan rate: 30 ~ 100 kHz
Vertical Refresh Scan Rate: 50 ~ 85 Hz
Lamp Type: Philips 330 W user replaceable P-VIP lamp
Lamp Life: 2,000 Hours (Standard), 2,500 Hours (ECO)
Keystone Correction:'+/-15 Degrees (Vertical) manual
Audio:Two Internal Speaker with 3 watts Output
Weight: 16.5 lbs (7.5Kg)
Wireless Dongle Compatible: YES
Input Interface: Analog RGB/Component Video (D-sub) x 2, Composite Video (RCA) x 1
S-Video (Mini DIN) x 1 , Component (3 RCA) x 1, HDMI (Video, Audio, HDCP) x 2, DVI (HDCP) x 1
PC Audio (Stereo mini jack) x 2, USB (Type A) x 2, USB (Mini B) x 1
Output Interface: Analog RGB (D-sub) x 1 , PC Audio (Stereo mini jack) x 1, SPDIF Audio (RCA) x 1
Control Interface: USB (Type B) x 1 / RS232 (Mini DIN) x 1 / Wired remote control port (Mini jack) x 1
12V DC (Screen control) x 1
Crestron Network Control & Remote Desktop
Dimension: 398 x 310 x 130 mm (15.7" x 12.2" x 5.1")
Remote Control (Infrared) with Laser Pointer & Page up/Page down Function
Power Supply: AC input 100~240V auto-switching power supply
Power Consumption: 440 Watts (Operation), 1 Watts (Standby, LAN off)
Operation Temperature: 5°C ~ 35°C / 41°F ~ 95°F
Noise Level: 33 dBA (Standard mode), 29 dBA (ECO mode)- w/o dust filter
Uniformity: 90%
Computer Compatability: IBM PC and Compatibles, Apple Macintosh and iMac (Wireless and Ethernet function exclusive),
and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA
WXGA (1280x800, 1280x768), UXGA (1600x1200), SXGA+ (1400x1050), SXGA (1280x1024),

(1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)

4717276033125	EY.K2701.001	P7500 - DLP™ - Full HD 1920 x 1080 - 40000:1 - 4000 ANSI Lumens - HDMIx2 - DVI - Lens Shift - LAN control - Usb - CBII+ - 7.5Kg - Zoom - Bag - ECO

Ultra Short Throw

Specifications

Display: DLP ™
Native XGA (1024x768), Maximum UXGA (1600 x 1200), WSXGA+ (1680 x 1050)
Aspect Ratio: 4:3 Native, 16:9 Compatible
Displayable Colors: 1.07 Billion Colors
Contrast Ratio: 4000:1
Brightness: 2500 ANSI Lumens (standard)
Digital Zoom: 2x
Projection lens: F = 2.6, f = 7.50mm, Manual Focus
Projection Screen Size (Diagonal): 40" (102cm) ~ 300" (762cm)
Projection Distance: 1.6' (0.5m) ~ 12.2' (3.7m)
Throw Ratio: 77"@95cm (0.61:1)
Horizontal Scan rate: 30k ~ 100k Hz
Vertical Refresh Scan Rate: 50 ~ 120 Hz
Lamp Type: Philips 190 W user replaceable UHP lamp
Lamp Life: 4,500 Hours (Standard), 6,000 Hours (ECO)
Keystone Correction: +/-40 Degrees (vertical)
Audio: One Internal Speaker with 2 watts Output
Weight: 5.9 lbs (2.7 Kg)
Wireless Dongle Compatible: NO
Input Interface: 2x D-Sub / Composite Video (RCA) / S-Video / HDMI (Video, HDCP) / PC Audio
Output Interface: Analog RGB (D-Sub), PC Audio (Stereo mini jack) x 1
Control Interface: RS232 (mini DIN) / USB (Mini-B) x 1
Dimension: 272 x 229 x 104 mm (10.7" x 9.0" x 4.0")
Remote Control: IR remote control with laser pointer & PgUp/PgDn functions
Power Supply: AC Input 100~240V auto-switching power supply
Power Consumption: 291 Watts (Operation), <1 Watts (Standby)
Operation Temperature: 0°C ~ 35°C / 32°F ~ 95°F
Noise Level: 31 dBA (Standard mode), 26 dBA (ECO mode)
Uniformity: 85%

Computer Compatability: IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Ethernet function exclusive), and VESA Standards WSXGA+ (1680x1050), WXGA+ (1440x900),
WXGA (1280x800, 1280x768), UXGA (1600x1200), SXGA+ (1400x1050), SXGA (1280x1024),
XGA (1024x768), SVGA (800x600), VGA (640x480)

Video Compatability: NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)

4717276695811 EY.JDW05.001 S1210 - DLP™ - XGA 1024 x 768 - 4000:1 - 2500 ANSI Lumens - Analog - 2x Digital Zoom - CBII+ - Autokeystone - 31dB - 2.7Kg - ECO

Specifications

Display: DLP ™
Native XGA (1024x768), Maximum UXGA (1600 x 1200), WSXGA+ (1680 x 1050)
Aspect Ratio: 4:3 Native, 16:9 Compatible
Displayable Colors: 1.07 Billion Colors
Contrast Ratio: 2500:1
Brightness: 3000 ANSI Lumens (standard)
3D ready: With DLP 3D ready, user can view any 120 Hz 3D frame sequential content from a PC with appropriate 120 Hz graphic card and 3D stereoscopic player or any HQFS 3D DVD title from an NTSC DVD player by wearing a DLP 3D glasses
Digital Zoom: 2x
Projection lens: F = 2.6, f = 7.50mm, Manual Focus
Projection Screen Size (Diagonal): 40" (102cm) ~ 300" (762cm)
Projection Distance: 1.6' (0.5m) ~ 12.2' (3.7m)
Throw Ratio: 161"@2m or 81"@1m (0.61:1)
Horizontal Scan rate: 30k ~ 100k Hz
Vertical Refresh Scan Rate: 50 ~ 120 Hz
Lamp Type: Osram 230 W user replaceable P-VIP lamp
Lamp Life: 2,500 Hours (Standard), 4,000 Hours (ECO)
Keystone Correction: +/-40 Degrees (vertical)
Audio: Two Internal Speaker with 5 watts Output (Equivalent to 10 watts speaker)
Weight: 7.7 lbs (3.5Kg)
Wireless Dongle Compatible: NO
Input Interface: 2x D-Sub / Composite Video (RCA) / S-Video / HDMI (Video, HDCP) / PC Audio
Output Interface: Analog RGB (D-Sub), PC Audio (Stereo mini jack) x 1
Control Interface: RS232 (mini DIN)
Dimension: 290 x 254 x 99 mm (11.4" x 10" x 3.9")
Remote Control: IR remote control with laser pointer & PgUp/PgDn functions
Power Supply: AC Input 100~240V auto-switching power supply
Power Consumption: 315 Watts (Operation), <1 Watts (Standby)
Operation Temperature: 5°C ~ 35°C / 41°F ~ 95°F
Noise Level: 33 dBA (Standard mode), 28 dBA (ECO mode)
Uniformity: 90%

Computer Compatability: IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Ethernet function exclusive), and VESA Standards WSXGA+ (1680x1050), WXGA+ (1440x900),
WXGA (1280x800, 1280x768), UXGA (1600x1200), SXGA+ (1400x1050), SXGA (1280x1024),
XGA (1024x768), SVGA (800x600), VGA (640x480)

Video Compatability: NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)

4717276275181 EY.JC905.003 S5201 - DLP™ - XGA 1024x768 - 2500:1 - 3000 ANSI Lumens - Analog & HDMI - 2x Digital Zoom - CBII+ - Short-Throw - DLP 3D - 33dB - 3.5Kg - Bag - Eco

Specifications

Display: DLP ™
Native XGA (1024x768), Maximum UXGA (1600 x 1200), WSXGA+ (1680 x 1050)
Aspect Ratio: 4:3 Native, 16:9 Compatible
Displayable Colors: 1.07 Billion Colors
Contrast Ratio: 3000:1
Brightness: 3000 ANSI Lumens (standard)
3D ready: With DLP 3D ready, user can view any 120 Hz 3D frame sequential content from a PC with appropriate 120 Hz graphic card and 3D stereoscopic player or any HQFS 3D DVD title from an NTSC DVD player by wearing a DLP 3D glasses
Digital Zoom: 2x
Projection lens: F = 2.6, f = 7.50mm, Manual Focus
Projection Screen Size (Diagonal): 40" (102cm) ~ 300" (762cm)
Projection Distance: 1.6' (0.5m) ~ 12.2' (3.7m)
Throw Ratio: 161"@2m or 81"@1m (0.61:1)
Horizontal Scan rate: 30k ~ 100k Hz
Vertical Refresh Scan Rate: 50 ~ 120 Hz
Lamp Type: Osram 230 W user replaceable P-VIP lamp
Lamp Life: 2,500 Hours (Standard), 4,000 Hours (ECO)
Keystone Correction: +/-40 Degrees (vertical)
Audio: Two Internal Speaker with 5 watts Output (Equivalent to 10 watts speaker)
Weight: 7.7 lbs (3.5Kg)
Wireless Dongle Compatible: YES
Input Interface: 2x D-Sub / Composite Video (RCA) / S-Video / HDMI (Video, HDCP) / PC Audio
Output Interface: Analog RGB (D-Sub), PC Audio (Stereo mini jack) x 1
Control Interface: RS232 (mini DIN)
Dimension: 290 x 254 x 99 mm (11.4" x 10" x 3.9")
Remote Control: IR remote control with laser pointer & PgUp/PgDn functions
Smart Pen: Acer Interactive Whiteboard Smart Pen included. The user can interact with the
projected image by direct touching the projected surface or remote at a distance.
Power Supply: AC Input 100~240V auto-switching power supply
Power Consumption: 315 Watts (Operation), <1 Watts (Standby)
Operation Temperature: 5°C ~ 35°C / 41°F ~ 95°F
Noise Level: 33 dBA (Standard mode), 28 dBA (ECO mode)

Uniformity: 90%

Computer Compatability: IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Ethernet function exclusive), and VESA Standards WSXGA+ (1680x1050), WXGA+ (1440x900),
WXGA (1280x800, 1280x768), UXGA (1600x1200), SXGA+ (1400x1050), SXGA (1280x1024),
XGA (1024x768), SVGA (800x600), VGA (640x480)

Video Compatability: NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)

[D] 4717276074630 EY.JBG05.001 S5201M - DLP™ - XGA 1024x768 - 3000:1 - 3000 ANSI Lumens - 2xHDMI - LAN control - Interactive Whiteboard - 2x Digital Zoom - CBII+ - Short-Throw - DLP 3D - 33dB - 3.5Kg - Bag - Eco

Specifications

Display: DLP ™
Native WXGA (1,280 x 800), Maximum UXGA (1600 x 1200), WSXGA+ (1680 x 1050)
Aspect Ratio: 16:10 (Native), 4:3, 16:9
Displayable Colors: 1.07 Billion Colors
Contrast Ratio: 4500:1
Brightness: 3,000 ANSI Lumens (Standard), 2,400 ANSI Lumens (ECO)
3D ready: With DLP 3D ready, user can view any 120 Hz 3D frame sequential content from a PC with appropriate 120 Hz graphic card and 3D stereoscopic player or any HQFS 3D DVD title from an NTSC DVD player by wearing a DLP 3D glasses
Digital Zoom: 2x
Projection lens: F = 2.6, f = 6.90mm, Manual Focus
Projection Screen Size (Diagonal): 47" (120cm) ~ 300" (762cm)
Projection Distance: 1.6' (0.5m) ~ 10.4' (3.2m)
Throw Ratio: 87"@92cm (0.49:1)
Horizontal Scan rate: 30k ~ 100k Hz
Vertical Refresh Scan Rate: 50 ~ 120 Hz
Lamp Type: Philips 230 W user replaceable UHP lamp
Lamp Life: 3,500 Hours (Standard), 5,000 Hours (ECO)
Keystone Correction: +/-40 Degrees (vertical)
Audio: Two Internal Speaker with 5 watts Output (Equivalent to 10 watts speaker)
Weight: 7.6 lbs (3.5Kg)
Wireless Dongle Compatible: YES
Input Interface: 2x D-Sub / Composite Video (RCA) / S-Video / HDMI (Video, HDCP) / PC Audio
Output Interface: Analog RGB (D-Sub), PC Audio (Stereo mini jack) x 1
Control Interface: RS232 (mini DIN)
Dimension: 290 x 254 x 99 mm (11.4" x 10" x 3.9")
Remote Control: IR remote control with laser pointer & PgUp/PgDn functions
Power Supply: AC Input 100~240V auto-switching power supply
Power Consumption: 352 Watts (Operation), <1 Watts (Standby, LAN off)
Operation Temperature: 5°C ~ 35°C / 41°F ~ 95°F
Noise Level: 33 dBA (Standard mode), 28 dBA (ECO mode)
Uniformity: 90%

Computer Compatability: IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Ethernet function exclusive), and VESA Standards WSXGA+ (1680x1050), WXGA+ (1440x900),
WXGA (1280x800, 1280x768), UXGA (1600x1200), SXGA+ (1400x1050), SXGA (1280x1024),
XGA (1024x768), SVGA (800x600), VGA (640x480)

Video Compatability: NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)

4717276276652 EY.JCD05.001 S5301WB - DLP™ - WXGA 1280x800 - 4500:1 - 3000 ANSI Lumens - Analog & HDMI - 2x Digital Zoom - CBII+ - Short-Throw - DLP 3D - 33dB - 3.5Kg - Bag - Eco

Specifications

Display: DLP ™
Native XGA (1024x768), Maximum UXGA (1600 x 1200), WSXGA+ (1680 x 1050)
Aspect Ratio: 4:3 Native, 16:9 Compatible
Displayable Colors: 1.07 Billion Colors
Contrast Ratio: 4200:1
Brightness: 2,500 ANSI Lumens (Standard), 2,000 ANSI Lumens (ECO)
3D ready: With DLP 3D ready, user can view any 120 Hz 3D frame sequential content from a PC with appropriate 120 Hz graphic card and 3D stereoscopic player or any HQFS 3D DVD title from an NTSC DVD player by wearing a DLP 3D glasses
Digital Zoom: 2x
Projection lens: F = 2.65, f = 3.50mm,Manual Focus
Projection Screen Size (Diagonal): 60" (152cm) ~ 300" (762cm)
Projection Distance: 1.0" (2.4cm) ~ 59" (149cm)
Throw Ratio: 77"@13cm (0.30:1)
Horizontal Scan rate: 30k ~ 100k Hz
Vertical Refresh Scan Rate: 50 ~ 120 Hz
Lamp Type: Philips 230 W user replaceable UHP lamp
Lamp Life: 3,500 Hours (Standard), 5,000 Hours (ECO)
Keystone Correction: +/-15 Degrees (Vertical), Manual
Audio: Two internal speaker with 10 watts output each
Weight: 15.4 lbs (7.0Kg)
Wireless Dongle Compatible: YES
Input Interface: 2x D-Sub / Composite Video (RCA) / S-Video / 2x HDMI (Video, HDCP) / PC Audio
/ 2x USB-A & 1x USB-B (mini)
Output Interface: Analog RGB (D-Sub), PC Audio (Stereo mini jack) x 1
Control Interface: USB (Mini-B) x 1, shared with the one of Input Interface & RS232 (mini DIN)
Dimension: 422 x 345 x 140 mm (16.6" x 13.6" x 5.5")
Remote Control: IR remote control with laser pointer & PgUp/PgDn functions
Power Supply: AC input 100~240V auto-switching power supply
Power Consumption: 380 Watts (Operation), <1 Watts (Standby, LAN off)
Operation Temperature: 5°C ~ 35°C / 41°F ~ 95°F

Noise Level: 33 dBA (Standard mode), 27 dBA (ECO mode)
Uniformity: 90%

IBM PC and Compatibles, Apple iMac/MacBook, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Ethernet function exclusive), and VESA Standards WSXGA+ (1680x1050), WXGA+ (1440x900),
WXGA (1280x800, 1280x768), UXGA (1600x1200), SXGA+ (1400x1050), SXGA (1280x1024),
XGA (1024x768), SVGA (800x600), VGA (640x480)

Video Compatability: NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)

[D] 4717276271732 EY.JC205.001 U5200 - DLP™ - XGA 1024x768 - 4200:1 - 2500 ANSI Lumens - Analog & Dual HDMI - USB-Slide show 2x Digital Zoom - CBII+ - Ultra-Short-Throw - Top Loading - 33dB - 3.5Kg - Eco

Home Cinema

Specifications

Display: DLP ™
Resolution: Native 720p (1,280 x 720)
Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)
Aspect Ratio: 16:9 Native, 4:3 Compatible
Displayable Colors: 1.07 Billion Colors
Contrast Ratio: 3200:1
Brightness: 2,500 ANSI Lumens (Standard), 2,000 ANSI Lumens (ECO)
3D ready: With DLP 3D ready, user can view any 120 Hz 3D frame sequential content from a PC with appropriate 120 Hz graphic card and 3D stereoscopic player or any HQFS 3D DVD title from an NTSC DVD player by wearing a DLP 3D glasses
Digital Zoom: 2x
Projection Lens: F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm
1:1.1 Manual Zoom and Manual Focus
Projection Screen Size (Diagonal): 0.67m ~7.62m
Projection Distance: 3.3' (1.0m) ~ 33.8' (10.3m)
Throw Ratio: 58"@2m (1.55 ~ 1.70:1)
Horizontal Scan rate: 31 ~ 100 kHz
Vertical Refresh Scan Rate: 56 ~ 120 Hz
Lamp Type: Osram 200 W user replaceable P-VIP lamp
Lamp Life: 3,000 Hours standard, 4,000 hours eco
Keystone Correction: +/-40 Degrees (vertical)
Audio: One Internal Speaker with 2 W Output
Weight: 4.9 lbs (2.2 Kg)
Wireless Dongle Compatible: NO
Input Interface: Analog RGB/Component Video (D-Sub) / Composite Video (RCA) / S-Video (mini DIN) /
Component (3x RCA) / HDMI (Video, HDCP) / PC Audio
Control Interface: RS232 (Mini DIN) x 1
Dimension: 268 x 192 x 80 mm (10.6" x 7.6" x 3.1")
Power Supply: AC Input 100~240V auto-switching power supply
Power Consumption: 245 Watts (operational) / <8 Watts (standby)
Operation Temperature: 5°C ~ 35°C
Noise Level: 32 dB in Standard Mode / 28 dB in Eco Mode
Uniformity: 85%
Computer Compatability:IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Ethernet function exclusive), and VESA Standards WSXGA+ (1680x1050), WXGA+ (1440x900),
WXGA (1280x800, 1280x768), UXGA (1600x1200), SXGA+ (1400x1050), SXGA (1280x1024),
XGA (1024x768), SVGA (800x600), VGA (640x480)

Video Compatability: NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)

4717276698591 EY.K0701.033 H5360 - DLP™ HD 720p - 1280 x 720 - 3200:1 - 2500Lm - Analog & HDMI - 2x Digital Zoom - CBII - 3D Vision Ready - 32dB - 2.2KG - BagEco

Specifications

Display: DLP ™
Resolution: Native 720p (1,280 x 720)
Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)
Aspect Ratio: 16:9 Native, 4:3 Compatible
Displayable Colors: 1.07 Billion Colors
Contrast Ratio: 3200:1
Brightness: 2,500 ANSI Lumens (Standard), 2,000 ANSI Lumens (ECO)
Blu-ray 3D ready: With the advanced HDMI 1.4a specification, the projector enables the display of a Blu-ray 1080p 3D title, delivery the theater-like enjoyment of Full HD 3D movie in your living room. All the mandatory 3D formats defined in HDMI 1.4a for 3D movie, game and broadcasting video, etc. are also supported.
Projection Lens: F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm
1:1.1 Manual Zoom and Manual Focus
Projection Screen Size (Diagonal): 0.67m ~7.62m
Projection Distance: 3.3' (1.0m) ~ 33.8' (10.3m)
Throw Ratio: 58"@2m (1.55 ~ 1.70:1)
Horizontal Scan rate: 31 ~ 100 kHz
Vertical Refresh Scan Rate: 56 ~ 120 Hz
Lamp Type: Osram 200 W user replaceable P-VIP lamp
Lamp Life: 3,000 Hours standard, 4,000 hours eco
Keystone Correction: +/-40 Degrees (vertical)
Audio: One Internal Speaker with 2 W Output
Weight: 4.9 lbs (2.2 Kg)
Wireless Dongle Compatible: NO
Input Interface: Analog RGB/Component Video (D-Sub) / Composite Video (RCA) / S-Video (mini DIN) /
Component (3x RCA) / HDMI (1.4a, Video, Audio, HDCP) x 1 / PC Audio

Control Interface: RS232 (Mini DIN) x 1
Dimension: 268 x 192 x 80 mm (10.6" x 7.6" x 3.1")
Power Supply: AC Input 100~240V auto-switching power supply
Power Consumption: 245 Watts (operational) / <8 Watts (standby)
Operation Temperature: 5°C ~ 35°C
Noise Level: 32 dB in Standard Mode / 28 dB in Eco Mode
Uniformity: 85%
Computer Compatability:IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Ethernet function exclusive), and VESA Standards WSXGA+ (1680x1050), WXGA+ (1440x900),
WXGA (1280x800, 1280x768), UXGA (1600x1200), SXGA+ (1400x1050), SXGA (1280x1024),
XGA (1024x768), SVGA (800x600), VGA (640x480)

Video Compatability: NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)

4717276698638 EY.JCC01.020 H5360BD - DLP™ HD 720p - 1280 x 720 - 3200:1 - 2500Lm - Analog & HDMI 1.4 - 2x Digital Zoom - CBII+ - Blu ray 3D, 2500Lm (DLP 3D Glasses Required) - 32dB - 2.2KG - BagEco

Specifications

Display: DLP ™
Resolution: Native 1080p (1,920 x 1,080)
Maximum UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)
Aspect Ratio: 16:9 Native, 4:3 Compatible
Displayable Colors: 1.07 Billion Colors
Contrast Ratio: 10.000:1
Brightness: 2,100 ANSI Lumens (Standard), 1,680 ANSI Lumens (ECO)
Projection Lens: F = 2.55 ~ 2.85, f = 22.41mm ~ 26.82mm
1:1.2 Manual Zoom and Manual Focus
Projection Screen Size (Diagonal): 38" (96cm) ~ 300" (762cm)
Projection Distance: 4.9' (1.5m) ~ 32.7' (10.0m)
Throw Ratio: 60"@2m (1.50 ~ 1.80:1)
Horizontal Scan rate: 31 ~ 100 kHz
Vertical Refresh Scan Rate: 56 ~ 120 Hz
Lamp Type: Osram 240 W user replaceable P-VIP lamp
3,500 Hours (Standard), 5,000 Hours (ECO), 6,000 Hours (ExtremeEco)*
Keystone Correction: +/-15 Degrees (Vertical), Manual
Audio: N/A
Weight: 5.6 lbs (2.54 Kg)
Wireless Dongle Compatible: NO
Input Interface: Analog RGB/Component Video (D-sub) x 1 / Composite Video (RCA) x 1 /
Component (3 RCA) x 1 / HDMI (Video, Audio, HDCP) x 2
Control Interface: USB (Type B) x 1 / 12V DC (Screen control) x 1
Dimension: 269 x 206 x 84 mm (10.6" x 8.1" x 3.3")
Power Supply: AC Input 100~240V auto-switching power supply
Power Consumption: 305W Watts (Operation), <1 Watts (Standby)
Operation Temperature: 5°C ~ 35°C
Noise Level: 34 dBA (Standard mode), 28 dBA (ECO mode)
Uniformity: 85%
Computer Compatability:IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Ethernet function exclusive), and VESA Standards WSXGA+ (1680x1050), WXGA+ (1440x900),
WXGA (1280x800, 1280x768), UXGA (1600x1200), SXGA+ (1400x1050), SXGA (1280x1024),
XGA (1024x768), SVGA (800x600), VGA (640x480)

Video Compatability: NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)

4717276677145 EY.JD501.001 H6500 - DLP™ FHD 1080p - 1920 x 1080 - 10.000:1 - 2100Lm - Analog & HDMI 1.3 - 2x Digital Zoom - CBII+ -34dB - 2.54KG - Bag - Extreme Eco

Specifications

Display: DLP ™
Resolution: Native Full HD 1080p (1920 x 1080)
Maximum UXGA (1600 x 1200), 1080P (1920 x 1080)
Aspect Ratio: 16:9 Native, 4:3 Compatible
Displayable Colors: 1.07 Billion Colors
Contrast Ratio: 40.000:1
Brightness: 2000 ANSI Lumens (Standard), 1600 ANSI Lumens (Eco)
Digital Zoom: 8x
Projection Lens: F = 2.55 ~ 2.87, f = 22.41mm ~ 26.82mm
1:1.2 Manual Zoom and Manual Focus
Projection Screen Size (Diagonal): 0.67m ~7.62m
Projection Distance: 4.9' (1.5m) ~ 32.9' (10.0m)
Throw Ratio: 60"@2m (1.51 ~ 1.83:1)
Horizontal Scan rate: 31 ~ 100 kHz
Vertical Refresh Scan Rate: 50 ~ 85 Hz
Lamp Type: Osram 230 W user replaceable P-VIP lamp
Lamp Life: 3,000 Hours (Standard), 4,000 Hours (ECO)
Keystone Correction: +/-20 Degrees (Vertical), Manual & Auto
Audio: One Internal Speaker with 2 watts Output
Weight: 6.5 lbs (3.0Kg)
Wireless Dongle Compatible: NO
Input Interface: Analog RGB/Component Video (D-Sub) / Composite Video (RCA) / S-Video (mini DIN) /
Component (3x RCA) / 2x HDMI (Video, HDCP) / PC Audio
Control Interface: USB (Type B) x 1 & RS232 (Mini DIN) x 1 12V DC (Screen control) x 1
Smart Detection: With the intelligent signal priority control, the signal detection time can be reduced dramatically.
Dimension: 294 x 229 x 100 mm (11.6" x 9.0" x 3.9")

Power Supply: AC input 100~240V auto-switching power supply
Power Consumption: 320 Watts (Operation), <1 Watts (Standby)
Operation Temperature: 5°C ~ 35°C / 41°F ~ 95°F
Noise Level: 29 dBA (Standard mode), 26 dBA (ECO mode)
Uniformity: 85%
Computer Compatability: IBM PC and Compatibles, (Wireless and
Ethernet function exclusive), and VESA Standards WSXGA+ (1680x1050), WXGA+ (1440x900),
WXGA (1280x800, 1280x768), UXGA (1600x1200), SXGA+ (1400x1050), SXGA (1280x1024),
XGA (1024x768), SVGA (800x600), VGA (640x480), 1080p (1,920x1,080),
Video Compatability: NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L),
HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)

4717276151119	EY.JBL01.001	H7531D - DLP™ FHD 1080p - 1920 x 1080 - 40.000:1 - 2000Lm - Analog & 2x HDMI - 8x Digital Zoom - 12VDC - CBII - CSII - Smartdetection - Dynamic Black - 29dB - 3.0KG - Bag - Eco

Specifications

Display: DLP ™
Resolution: Native Full HD 1080p (1920 x 1080)
Maximum UXGA (1600 x 1200), 1080P (1920 x 1080)
Aspect Ratio: 16:9 Native, 4:3 Compatible
Displayable Colors: 1.07 Billion Colors
Contrast Ratio: 40.000:1
Brightness: 2000 ANSI Lumens (Standard), 1600 ANSI Lumens (Eco)
Digital Zoom: 8x
Projection Lens: F = 2.55 ~ 2.87, f = 22.41mm ~ 26.82mm
1:1.2 Manual Zoom and Manual Focus
Projection Screen Size (Diagonal): 0.67m ~7.62m
Projection Distance: 4.9' (1.5m) ~ 32.9' (10.0m)
Throw Ratio: 60"@2m (1.51 ~ 1.83:1)
Horizontal Scan rate: 31 ~ 100 kHz
Vertical Refresh Scan Rate: 50 ~ 85 Hz
Lamp Type: Osram 230 W user replaceable P-VIP lamp
Lamp Life: 3,000 Hours (Standard), 4,000 Hours (ECO)
Keystone Correction: +/-20 Degrees (Vertical), Manual & Auto
Audio: One Internal Speaker with 2 watts Output
Weight: 15.9 lbs (7.2Kg)
Wireless Dongle Compatible: NO
Input Interface: Analog RGB/Component Video (D-Sub) / Composite Video (RCA) / S-Video (mini DIN) /
Component (3x RCA) / 2x HDMI (Video, HDCP) / PC Audio
Control Interface: USB (Type B) x 1 & RS232 (Mini DIN) x 1 12V DC (Screen control) x 1
Smart Detection: With the intelligent signal priority control, the signal detection time can be reduced dramatically.
Dimension: 294 x 229 x 100 mm (11.6" x 9.0" x 3.9")
Power Supply: AC input 100~240V auto-switching power supply
Power Consumption: 320 Watts (Operation), <1 Watts (Standby)
Operation Temperature: 5°C ~ 35°C / 41°F ~ 95°F
Noise Level: 29 dBA (Standard mode), 26 dBA (ECO mode)
Uniformity: 85%
Computer Compatability: IBM PC and Compatibles, (Wireless and
Ethernet function exclusive), and VESA Standards WSXGA+ (1680x1050), WXGA+ (1440x900),
WXGA (1280x800, 1280x768), UXGA (1600x1200), SXGA+ (1400x1050), SXGA (1280x1024),
XGA (1024x768), SVGA (800x600), VGA (640x480), 1080p (1,920x1,080),
Video Compatability: NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L),
HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)

4717276614027	EY.JDG01.001	H9500BD - DLP™ FHD 1080p - 1920 x 1080 - 3D - 50.000:1 - 2000Lm - Analog, DVI & 2x HDMI - 8x Digital Zoom - - CBII - CSII - Smartdetection - Dynamic Black - 30dB - 7.2KG - Bag - Eco

Pico / LED Projector

Specifications

Display: DLP ™
Resolution: Native SVGA 600p (854 x 600)
Maximum SXGA (1,280 x 1,024), WXGA+ (1,440 x 900)
Aspect Ratio: 4:3 (Native), 16:9 compatible
Displayable Colors: 16.7 Million Colors
Contrast Ratio: 2000:1
Brightness: 200 ANSI Lumens (LED)
Digital Zoom: N/A
Projection Lens:F = 2.0, f = 17.67mm Manual Focus
1:1.1 Manual Zoom and Manual Focus
Projection Screen Size (Diagonal): 24" (60cm) ~ 100" (254cm)
Projection Distance: 3.3' (1.0m) ~ 13.9' (4.2m)
Throw Ratio: 47"@2m (2.04:1)
Horizontal Scan rate: 31k ~ 69k Hz
Vertical Refresh Scan Rate: 50 ~ 85 Hz
Lamp Type: PhlatLight® LEDs
Lamp Life: 20,000 Hours
Keystone Correction: +/-40 Degrees (Vertical), Manual & Auto
Audio: N/A
Weight: 0.55 Kg
Wireless Dongle Compatible: NO
Input Interface: Analog RGB/Component Video (D-sub) x 1 /
Component Composite Video (RCA) x 1
HDMI (Video, Audio, HDCP) x 1 / USB (Type A) x 1 / SD (SDHC) x 1
Control Interface: N/A
Dimension: 122 x 116 x 42 mm (4.8" x 4.6" x 1.7")
Power Supply: DC input 19V via a 90W power adapter (AC input 100~240V auto-switching to DC 19V)

Power Consumption: 55 Watts (Operation), <1 Watts (Standby)
Remote Control: IR remote control
Operation Temperature: 5°C ~ 35°C / 41°F ~ 95°F
Noise Level: 36 dBA (Standard mode), 32 dBA (ECO mode)
Uniformity: 85%
Computer Compatability: IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)

Video Compatability: NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i), EDTV (480p, 576p), SDTV (480i, 576i)

4717276027926 EY.K2801.001 K11 LED - DLP™ SVGA 858 x 600 - 2000:1 - 200 ANSI Lumens - HDMI - USB - SD - 20.000h lamp lifetime - 28dB - 0.55KG - Bag

Specifications

Display: DLP ™
Resolution: Native WVGA (854 x 480)
Maximum WXGA (1,280 x 800)
Aspect Ratio: 16:9 (Native), 4:3
Contrast Ratio: 1000:1
Displayable Colors: 16.7 Million Colors
Brightness:100 ANSI Lumens (Standard) , 75 ANSI Lumens (ECO), 60 ANSI Lumens (USB max.)
Projection Lens: F = 1.87, f = 11.00mm
1:1.1 Manual Zoom and Manual Focus
Projection Screen Size (Diagonal): 10" (25cm) ~ 100" (254cm)
Projection Distance: 1.2' (0.4m) ~ 12.0' (3.7m)
Horizontal Scan rate: 30k ~ 50k Hz
Vertical Refresh Scan Rate: 50 ~ 60 Hz
Lamp Type: RGB LED
lamp Life: 20,000 Hours
Weight: 180 grams
Wireless Dongle Compatible: NO
Display over USB (DoUSB, USB3.0)
Computer Input: Powered by USB USB (3.0 & 2.0, Micro-B) x 1
Dimensions: 120 x 82 x 25.7 mm (4.7" x 3.2" x 1.0")
Power Supply: AC to DC power adapter
Power Consumption: 20 Watts (Operation), <0.5 Watts (Standby)
Operation Temperature: 5°C ~ 40°C / 41°F ~ 104°F
Noise Level: 30 dBA (Standard mode), 24 dBA (ECO mode)
Uniformity: 85%
IBM PC and Compatibles, Apple iMac/MacBook, and VESA Standards WXGA (1,280 x 800, 1,280 x 768, 1,280 x 720), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)

4717276722883 EY.JE001.001 C120 LED - WVGA 854 x 480 - 1000:1 - 100 Lm - RGB LED - Display & power over USB - USB 2.0/3.0 & Micro-B - 180g - protection case

Specifications

Display: DLP ™
Native WXGA (1280 x 800)
Maximum UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)
Aspect Ratio: 16:10 (Native), 4:3, 16:9
Contrast Ratio: 10.000:1
Displayable Colors: 1.07 Billion Colors
Brightness: 300 ANSI Lumens (Standard), 210 ANSI Lumens (ECO)
Projection Lens: F = 2.0, f = 14.95mm Manual Focus
1:1.1 Manual Zoom and Manual Focus
Projection Screen Size (Diagonal): 17" (43cm) ~ 100" (254cm)
Projection Distance: 1.8' (0.6m) ~ 10.6' (3.2m) / 62"@2m (1.50:1)
Horizontal Scan rate: 30k ~ 100k Hz
Vertical Refresh Scan Rate: 50 ~ 120 Hz
Lamp Type: RGB LEDs
lamp Life: 20,000 Hours
Weight: 0.95 lbs (0.43 Kg)
Wireless Dongle Compatible: YES
USB Reader: With the USB reader, the projector provides the full access of multimedia contents
Computer Input: 1x Composite Video (RCA) / 1x USB-A & 1x USB-B (mini), SD Card HDMI (Video, Audio, HDCP) x 1
PC Audio (Stereo Mini Jack)
Dimensions: 140 x 116 x 41 mm (5.5" x 4.6" x 1.6")
IR Remote Control
Power Supply: DC input 19V via a 65W power adapter (AC input 100~240V auto-switching to DC 19V)
Power Consumption: 65 Watts (Operation), <0.5 Watts (Standby)
Operation Temperature: 5°C ~ 35°C / 41°F ~ 95°F
Noise Level: 35 dBA (Bright mode), 33 dBA (Standard mode), 29 dBA (ECO mode)
Uniformity: 90%
IBM PC and Compatibles, Apple iMac/MacBook, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)

4717276863562 EY.JE601.001 K130 LED - DLP WXGA 1280 x 800 - 300 Lumens - 10.000:1 - Smartphone compatible - HDMI - USB & SD - 29dB - 1.24Kg

Specifications

Display: DLP ™
Native WXGA (1280 x 800)
Maximum UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)
Aspect Ratio: 16:10 (Native), 4:3, 16:9
Contrast Ratio: 4000:1
Displayable Colors: 1.07 Billion Colors
Brightness: 500 ANSI Lumens (Standard), 350 ANSI Lumens (ECO)
Projection Lens: F = 1.5, f = 13.92mm Manual Focus
1:1.1 Manual Zoom and Manual Focus
Projection Screen Size (Diagonal): 30" (76cm) ~ 100" (254cm)
Projection Distance: 3.0' (0.9m) ~ 9.9' (3.0m)
Horizontal Scan rate: 30k ~ 100k Hz

Vertical Refresh Scan Rate: 50 ~ 120 Hz
Lamp Type: PhlatLight® LEDs
lamp Life: 20,000 Hours
Weight: 2.73 lbs (1.24 Kg)
Wireless Dongle Compatible: YES
USB Reader: With the USB reader, the projector provides the full access of multimedia contents
Computer Input: 1x Composite Video (RCA) / 1x USB-A & 1x USB-B (mini), SD Card HDMI (Video, Audio, HDCP) x 1
PC Audio (Stereo Mini Jack)
Dimensions: 218 x 168 x 46.5 mm (8.6" x 6.6" x 1.8")
IR Remote Control
Power Supply: AC input 100~240V auto-switching power supply
Power Consumption: 120 Watts (Operation), <1 Watts (Standby)
Operation Temperature: 5°C ~ 35°C / 41°F ~ 95°F
Noise Level: 35 dBA (Bright mode), 33 dBA (Standard mode), 29 dBA (ECO mode)
Uniformity: 85%
IBM PC and Compatibles, Apple iMac/MacBook, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)

4717276393199 EY.JCN01.001 K330 LED - DLP WXGA 1280 x 800 - 500 Lumens - 4000:1 - True24P - HDMI - USB Multimedia & SD cardreader - 29dB - 1.24Kg

Specifications

Display: DLP ™
Native XGA (1,024 x 768)
Maximum UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)
Aspect Ratio: 4:3 (Native), 16:9, 16:10
Contrast Ratio: 100.000:1
Displayable Colors: 1.07 Billion Colors
Brightness: 2000 ANSI Lumens (Standard), 1600 ANSI Lumens (ECO)
Projection Lens: F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm
1:1.1 Manual Zoom and Manual Focus
Projection Screen Size (Diagonal): 27" (70cm) ~ 300" (762cm)
Projection Distance: 3.9' (1.2m) ~ 39.0' (11.9m)
Horizontal Scan rate: 30k ~ 100k Hz
Vertical Refresh Scan Rate: 50 ~ 120 Hz
Lamp Type: Laser & LED Hybrid
lamp Life: 20,000 Hours
Weight: 8.9 lbs (4.04 Kg)
Wireless Dongle Compatible: NO
USB Reader: With the USB reader, the projector provides the full access of multimedia contents
Computer Input: 1x Composite Video (RCA) / 1x USB-A & 1x USB-B (mini), SD Card HDMI (Video, Audio, HDCP) x 1
PC Audio (Stereo Mini Jack)
Dimensions: 321 x 231 x 87 mm (12.6" x 9.1" x 3.4")
IR remote control with mouse & PgUp/PgDn functions and backlight
Power Supply: AC input 100~240V auto-switching power supply
Power Consumption: 215W Watts (Operation), <0.5 Watts (Standby)
Operation Temperature: 5°C ~ 40°C / 41°F ~ 104°F
Noise Level: 32 dBA (Standard mode), 29 dBA (ECO mode)
Uniformity: 95%
IBM PC and Compatibles, Apple iMac/MacBook, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)

[D] 4712196076498 MR.JES11.001 K520 - LASER / LED Hybrid DLP XGA 1024 x 768 - 2000 Lumens - 100.000:1 - True24P - HDMI - 33dB - 4.04Kg

Specifications

Display: DLP ™
Native Full HD 1080P (1920 x 1080)
Maximum UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)
Aspect Ratio: 16:9 (Native), 4:3
Contrast Ratio: 100.000:1
Displayable Colors: 1.07 Billion Colors
Brightness: 1,500 ANSI Lumens (Standard), 1,200 ANSI Lumens (ECO)
Projection Lens: F = 2.55 ~ 2.86, f = 22.37mm ~ 26.73mm
1:1.2 Manual Zoom and Manual Focus
Projection Screen Size (Diagonal): 38" (96cm) ~ 300" (762cm)
Projection Distance: 4.9' (1.5m) ~ 32.7' (10.0m)
Horizontal Scan rate: 30k ~ 100k Hz
Vertical Refresh Scan Rate: 50 ~ 85 Hz
Lamp Type: Laser & LED Hybrid
lamp Life: 20,000 Hours
Weight: 8.9 lbs (4.04 Kg)
Wireless Dongle Compatible: NO
USB Reader: With the USB reader, the projector provides the full access of multimedia contents
Computer Input: 1x Composite Video (RCA) / 1x USB-A & 1x USB-B (mini), SD Card HDMI (Video, Audio, HDCP) x 1
PC Audio (Stereo Mini Jack) 2x HDMI
Dimensions: 321 x 231 x 87 mm (12.6" x 9.1" x 3.4")
IR remote control with mouse & PgUp/PgDn functions and backlight
Power Supply: AC input 100~240V auto-switching power supply
Power Consumption: 215W Watts (Operation), <0.5 Watts (Standby)
Operation Temperature: 5°C ~ 40°C / 41°F ~ 104°F
Noise Level: 30 dBA (Standard mode), 27 dBA (ECO mode)
Uniformity: 95%
IBM PC and Compatibles, Apple iMac/MacBook, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)

4712196127626 MR.JEH11.001 K750 - LASER / LED Hybrid DLP XGA 1920 x 1080 FHD - 1500 Lumens - 100.000:1 - True24P - 8x Digital Zoom - 2x HDMI - 30dB - 4.04Kg

Options Projector

	4717276014636	EC.K0700.001	H5360/H5360BD Lamp
	4717276677121	EC.JD500.001	H6500 Lamp
	4712842850083	EC.J9900.001	H7530 / H7530D / H7531D Lamp
	4717276270537	EC.JC200.001	U5200 Lamp
	4717276275983	EC.JC300.001	H9500 Lamp
	4717276016562	EC.K1500.001	P1100/A/B/C, P1200/A/B/i/n Lamp
	4717276274375	EC.JC600.001	P1101/P1201 Lamp
	4717276016586	EC.K1700.001	P1203/P1303W/P1206 Lamp
	4717276465834	EC.JCR00.001	P1203P/PB/Pi/P1206P/P1303PW Lamp
	4718235684044	EC.J6700.001	P3150/P3250/3251 Lamp
	4712842421825	EC.J8700.001	P5271/P5271i Lamp
	4717276027810	EC.K2400.001	P7200i Lamp
	4717276027704	EC.K2500.001	P7203 Lamp
	4717276208295	EC.JBM00.001	P7205 Lamp
	4717276011970	EC.J6400.002	P7290 Lamp
	4717276033118	EC.K2700.001	P7500 Lamp
	4717276683665	EC.JDW00.001	S1210 Lamp
	4717276074623	EC.JBG00.001	S5201M Lamp
	4717276275068	EC.JC900.001	S5201/S5201B/S5301WB Lamp
	4717276293697	EC.JC800.001	S5201WM Lamp
	4717276030773	EC.K3000.001	X1110/X1110A/X1210K/X1210/X1210S Lamp
	4717276455842	EC.JCQ00.001	X1111/X1111A/X1211/X1311HW&KW Lamp
	4717276251475	EC.JBU00.001	X1161P/X1261P/X110P Lamp
	4712842655817	EC.K0100.001	X1161/X1261/X110 Lamp
[N]	4712196020170	MC.40111.001	X1140/X1140A/X111/X1240 Lamp
	4717276091620	EC.JBJ00.001	X1213 Lamp
	4717276483289	EC.JD300.001	X1213P Lamp
	4717276555283	EC.JD700.001	P1120H/P1220H/P1320WH Lamp
	4712842188148	JZ.J7400.001	F80-S01 80inch 4:3 Floor Pull UP Projection Screen
	4717276034542	JZ.J7400.002	70x70" Wall & Ceiling Matt White Manual Screen

	4717276270339	JZ.JBT00.002	P15-S01 Projection Screen Portable Screen 15" with Gain 3.2
	4718235233273	EZ.PCM03.007	Universal Ceiling Mount Kit adjustable from 13.5cm to 76.5cm.
	4717276245450	JZ.JBG00.002	Acer Smart Pen for Acer Interactive Projector
	4717276272036	JZ.JBT00.004	C20 optional 3 in 1 accesory pack: remote control + Dexim adapter for iPod/iPhone + Tripod, EMEA
	4717276445508	JZ.JBG00.003	Acer IWB 77-S01 Interactive WhiteBoard, 77", 4,3
	4717276272821	JZ.JBG00.006	Acer IWB 77-S01 Interactive White Board 77", 4,3, Version 2
	4717276272821	JZ.JBG00.005	Acer SWM01 Wall Mount for Ultra-Short Throw Projector
	4717276270278	JZ.JBF00.001	USB wireless adapter 802.11b/g/n
	4717276272203	JZ.JC400.001	C112 Battery Set (BT-K01)
[E]	4717276563226	JZ.JCP00.001	P25-W1 Projection Screen Portable Screen 25" with Gain 2.0 for C110
[N]	4717276530891	JZ.JBG00.008	Interactive Whiteboard Pen